

PRIOCONT

Fire-Resistant Container



Fire-resistant container to store two IBC containers or six 200l barrels on Euro pallets. The homogeneous, solid material has high-quality, easy to clean interior and exterior surfaces. The base has sufficient clearance to drive a forklift underneath for transportation. The container is smoke proof in accordance with DIN 18095 and offers a fire resistance of 90 minutes.

Function

- Complies with the requirements of the Technical Regulations for Hazardous Material 510, Act on the Regulation of Matters Relating to Water, Hazardous Materials Safety Regulations,
- Fire resistance 90 minutes: fire resistant
- EI 90/F 90 classification
- Expert opinion by an official material testing institute



■ Electrical door hold-open system



■ Ventilation flap, top view



■ Door hold-open system with holding magnet



■ Door hinge in stainless steel



■ Explosion protected smoke detector



■ Tandem door closer

Construction & Equipment

- Container of high mechanical resistance
- Single layer wall structure of homogeneous solid material
- Galvanized base drip pan for environmental protection according to the Water Resources Law § 19
- Dimensions optimized for IBC containers and Euro palettes
- Door(s) with 3D stainless steel strips, 3-point locking system and profile semi-cylinder
- Electrical door hold-open system with flexible and adjustable door opening angle up to 120°
- Smoke triggered fire detection for automatic door closure
- Closing sequence control
- Explosion-protected electrical system
- Ventilation openings on the top side, DN 100 - closure via fire dampers
- Shelves with hot-dip galvanised grates

Material & Surface


- Standard surface CP laminate
- Building material with surface coating, classified A2 – s1, d0: non-combustible
- Colour light grey, similar to RAL 7035




Scope of delivery

- Sump
- Tandem door closer
- Door coordinator incl. door damper

PRIOCONT – Fire-resistant container

PRIOCONT 2-IBC



Art.	 H x W x D mm	 H x W x D mm	 incl. equipment kg	Storage volume Litres	Equipment	Description
90 minutes fire resistance						
PCO-2-IBC-TYP1	2839 x 3128 x 1637	1976 x 3020 x 1550	2850	2 x IBC / 3 Euro pallet with 6 x 200 litre drums	1000	unmounted on pallets
PCO-2-IBC					Drain pan	preassembled

You can find tender texts at: www.priorit.de

Options and accessories

- Doors or entire body in alternative RAL colours / surfaces, on request
- Design with anti-burglary protection according to WK 2



■ Fire resistant cable compartment



■ Assembly on-site

Art.	Accessories
Pipe and cable bulkheads	
KRS125	Cable and pipe compartment d = 135 mm
EKRD90-014-014	Single cable and pipe-penetration
Door accessories	
EP.B.8716	Single cylinder keyed-differently without rosette
EP.B.8718	Single cylinder KABA simultaneous locking without rosette
EP.B.8965	Separated square shaft, 9 mm, L = 130 mm with panic hardware
EP.B.7976	Door handle set stainless steel
Assembly	
PCO-2-Mont	Assembly on-site by PRIORIT